



COPPER-FIN II[®] WATER HEATER PRODUCT SUMMARY

(CF) 400,000 - 2,070,000 BTU/HR

	CF-0402	CF-0502	CF-0652	CF-0752	CF-0992	CF-1262	CF-1442	CF-1802	CF-2072
WATER									
GALLON CAPACITY	1.5	1.7	1.9	2.0	3.4	3.7	4.1	4.5	4.8
HEATING SURFACE (SQ. FT.)	46.9	59.0	76.8	88.1	96.0	120.2	144.0	176.0	200.0
WATER CONNECTIONS	2"	2"	2"	2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"	2-1/2"
DRAIN	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
WATER FLOW RATE (GPM)	55	55	55	55	90	90	90	90	90
HEAD LOSS (FT. OF HD.)	6.4	6.5	6.7	6.8	5.8	6.6	7.2	8.4	9.2
MAX. WORKING PRESSURE (PSI)	160	160	160	160	160	160	160	160	160
MAX. WATER HARDNESS (GRAINS)	25	25	25	25	25	25	25	25	25
GPH @ 70°F RISE	589	736	957	1,104	1,457	1,855	2,120	2,650	3,047
GPH @ 100°F RISE	412	515	670	773	1,020	1,298	1,484	1,855	2,133
GPH @ 140°F RISE	294	368	479	552	729	927	1,060	1,325	1,524
# OF RELIEF VALVES	1	1	1	1	1	1	1	1	2
RELIEF VALVE SIZE	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"	3/4"
RELIEF VALVE RATING (MBH)	500	1,912	1,912	1,912	1,912	1,912	1,912	1,912	1,912
RELIEF VALVE PRESSURE RATING (PSI)	150	150	150	150	150	150	150	150	150
RELIEF VALVE TEMPERATURE RATING (°F)	210	210	210	210	210	210	210	210	210
GAS									
INLET CONNECTION	1-1/4"	1-1/4"	1-1/4"	1-1/4"	2"	2"	2"	2"	2"
MAX. INLET PRESSURE, NAT	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.
MIN. INLET PRESSURE, NAT	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.	4.5" w.c.
MANIFOLD PRESSURE, NAT	1.8" w.c.	1.8" w.c.	1.8" w.c.	1.8" w.c.	1.2" w.c.	1.2" w.c.	1.2" w.c.	1.2" w.c.	1.2" w.c.
MAX. INLET PRESSURE, LP	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.	14" w.c.
MIN. INLET PRESSURE, LP	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.	8.0" w.c.
MANIFOLD PRESSURE, LP	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.	4.6" w.c.
MAX. BTU/HR INPUT	399,999	500,000	650,000	750,000	990,000	1,260,000	1,440,000	1,800,000	2,070,000
MIN. BTU/HR INPUT	250,000	250,000	250,000	250,000	360,000	360,000	360,000	360,000	630,000
ELECTRICAL									
VOLTAGE/PUMP	120	120	120	120	120	120	120	120	120
VOLTAGE/CONTROL	24	24	24	24	24	24	24	24	24
TOTAL AMPS W/PUMP	12.1	12.1	14.6	14.6	17.9	17.9	21.4	21.4	21.4
# OF ELECTRICAL CONNECTIONS	2	2	2	2	2	2	2	2	2
DIMENSIONS									
HEIGHT	31-1/2"	31-1/2"	31-1/2"	31-1/2"	36"	36"	36"	36"	36"
WIDTH (INCLUDES PUMP)	56-1/4"	64"	75-1/4"	82-1/2"	68-3/4"	79"	89-1/4"	102-3/4"	113"
DEPTH	22-1/4"	22-1/4"	22-1/4"	22-1/4"	33-1/2"	33-1/2"	33-1/2"	33-1/2"	33-1/2"
SERVICE CLEARANCES									
FRONT	30"	30"	30"	30"	30"	30"	30"	30"	30"
BACK	3"	3"	3"	3"	3"	3"	3"	3"	3"
RIGHT SIDE	3"	3"	3"	3"	3"	3"	3"	3"	3"
LEFT SIDE (PIPING)	24"	24"	24"	24"	24"	24"	24"	24"	24"
TOP	3"	3"	3"	3"	3"	3"	3"	3"	3"
VENTING									
SIZE	6"	6"	8"	8"	10"	12"	12"	14"	14"
VENT CATEGORY	I	I	I	I	I	I	I	I	I
VENT MATERIAL	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT	B-VENT
MAXIMUM DRAFT	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.	-0.08" w.c.
MINIMUM DRAFT	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.	-0.02" w.c.

Lochinvar, LLC • 300 Maddox Simpson Pkwy • Lebanon, TN 37090 • 615-889-8900 / Fax: 615-547-1000
www.Lochinvar.com