



## CREST BOILER PRODUCT SUMMARY

(FB) 2,500,000 - 6,000,000 BTU/HR

	FB-2500	FB-3000	FB-3500	FB-4000	FB-5000	FB-6000
<b>WATER</b>						
GALLON CAPACITY	161	181	215	291	380	380
HEATING SURFACE (SQ. FT.)	195.0	237.0	272.0	382.0	483.0	483.0
INLET WATER CONNECTION	4" Flanged	4" Flanged	4" Flanged	4" Flanged	4" Flanged	6" Flanged
OUTLET WATER CONNECTION	4" Flanged	4" Flanged	4" Flanged	4" Flanged	4" Flanged	6" Flanged
DRAIN	1.5	1.5	1.5	1.5	1.5	1.5
MAXIMUM FLOW RATE	350	350	350	350	350	550
MINIMUM FLOW RATE	25	25	45	45	50	50
20°F ΔT WATER FLOW (GPM)	230.0	277.0	323.0	350†	350††	550.0
HEAD LOSS (FT. OF HD.)	4.6	5.6	7.5	3.2	6.5	5.4
40°F ΔT WATER FLOW (GPM)	115.0	138.0	161.0	190.0	237.0	276.0
HEAD LOSS (FT. OF HD.)	1.3	1.2	1.2	1.6	3.1	4.8
MAX. WORKING PRESSURE (PSI)	160	160	160	160	160	160
# OF RELIEF VALVES	1	1	1	1	1	1
RELIEF VALVE SIZE	1.5	1.5	2.0	2	2	2.5
RELIEF VALVE RATING (MBH)	3,075,000	3,075,000	4,237,000	4,100,000	5,100,000	7,672,000
RELIEF VALVE PRESSURE RATING (PSI)	50	50	50	50	50	50
<b>GAS</b>						
BTU/HR INPUT	2,500,000	3,000,000	3,500,000	4,000,000	5,000,000	6,000,000
BTU/HR OUTPUT (HIGH FIRE)	2,300,000	2,760,000	3,220,000	3,720,000	4,650,000	5,520,000
BTU/HR OUTPUT (LOW FIRE)	115,000	138,000	179,000	310,000	465,000	552,000
HORSE POWER (INPUT)	75	90	105	119	149	179
INLET CONNECTION	2	2	2	2.5	2.5	2.5
MAX. INLET PRESSURE, NAT	14	14	14	14	14	14
MIN. INLET PRESSURE, NAT	4	4	4	4	4	4
MAX. INLET PRESSURE, LP	14	14	14	14	14	14
MIN. INLET PRESSURE, LP	4	4	4	4	4	4
<b>ELECTRICAL *</b>						
VOLTAGE/HEATER (VAC)	120/1PH	120/1PH	120/1PH	208/3PH	208/3PH	208/3PH
VOLTAGE/CONTROL (VAC)	24	24	24	24	24	24
TOTAL AMPS	10.2	13.6	19.7	14	14	14
<b>DIMENSIONS</b>						
HEIGHT	80	80	80	80	80	80
WIDTH	34 1/4	40 1/2	40 1/2	53.75	53.75	53.75
DEPTH	76.375	83 5/8	83 1/4	109	109	109
SHIPPING WEIGHT (lbs.)	2,560	2,920	3,225	4,750	5,500	5,500
OPERATING WEIGHT (lbs.)	3,652	4,126	4,744	6,900	8,000	8,000
<b>SERVICE CLEARANCES (RECOMMENDED)</b>						
FRONT	30	30	30	30	30	30
REAR	24	24	24	24	24	24
RIGHT SIDE	24	24	24	24	24	24
LEFT SIDE	24	24	24	24	24	24
TOP	24	24	24	24	24	24
<b>DIRECT VENTING</b>						
VENT SIZE	9	10	10	12	14	14
AIR INLET SIZE	8	10	10	12	14	14
VENT CATEGORY	IV	IV	IV	IV	IV	IV
VENT MATERIAL	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel	Stainless Steel

\* Electrical - For alternate voltages and amp draws, please consult the factory or the installation and operation manual.

† Data based on 21°F delta T

†† Data based on 27°F delta T

Lochinvar LLC • 300 Maddox Simpson Pkwy • Lebanon, TN 37090 • 615-889-8900 / Fax: 615-547-1000  
www.Lochinvar.com