



Stack Frame for Pool Heaters

Pre-Assembled Welded Construction – No Field Assembly Required

Match Load And Capacity

With this versatile stand, you can stack AQUAS Pool Packages, Copper-Fin2 and Energyrite Pool Heaters to achieve the perfect Btu/hr capacity for each application.

For example, a facility needs a Copper-Fin2 pool heater with a total capacity of 1.6 million Btu/hr. Instead of installing an oversized CPN1802 unit or a smaller CPN1442 model, now you can combine two units – CPN992 and CPN652 models – to exactly match the facility’s needs.

Plus, the total footprint of this combined system is just over 10 inches wider than the CPN652 unit alone, making it smaller than either the CPN1802 or CPN1442 model. All thanks to the Lochinvar Stack Frame.


No Assembly Required

Lochinvar’s Stack Frame is fully factory assembled and shipped in one piece. The frame is welded using square steel tubing by certified welders ensuring integrity for the life of the frame.



Two Lochinvar 990,000 Btu/hr Copper-Fin2 pool heaters stacked for a total capacity of almost 2 million Btu/hr.

Copper-Fin2® Pool Heaters (Models 502-2072)




MODEL #	PART #	A*	B**	C	Wt. (lbs.)
CP 502	MSF30003	73-1/2"	59"	24-1/2"	88
CP 652	MSF30004	73-1/2"	80"	24-1/2"	150
CP 752	MSF30004	73-1/2"	80"	24-1/2"	150
CP 992	MSF30005	88"	75"	36"	191
CP 1262	MSF30006	88"	95"	36"	237
CP 1442	MSF30006	88"	95"	36"	237
CP 1802	MSF30007	88"	119"	36"	286
CP 2072	MSF30007	88"	119"	36"	286

Note: Heater height is 31-1/2" (502-752) & 36" (992-2072).

*Allow space for vent connection. **Allow space for plumbing connections.

EnergyRite® Pool Heaters (Models 152-402)



MODEL #	PART #	A	B**	C*	Wt. (lbs.)
ER 152-402	MSF3052	77-1/2"	47"	26"	85

** Allow space for plumbing connections.

NOTE: Stack Frames are for indoor applications only.



Lochinvar, LLC
300 Maddox Simpson Parkway
Lebanon, Tennessee 37090
P: 615.889.8900 / F: 615.547.1000
f t i n p Lochinvar.com